



-18°C ÷ +80°C



Working pressure:
12 Bar



Compressed air



Parallel gas BSPP ISO 228
G1/8" and G1/4"



Body: Nickel-plated brass
Spring: Nickel-plated steel

PROFILE - MINI SERIES



NOMINAL DIAMETER

4,8 mm

AIR FLOWRATE

1100 l/min



Products in compliance with
EC Regulation 1907/2006



Products in compliance with
the directive EU 2015/863

VIEW - QUICK COUPLING 8110FM



8110FM

Male quick coupling BSPP thread



CODE	THREAD	LENGTH	WRENCH
8110FM01	G 1/8"	38,9	14
8110FM02	G 1/4"	37,7	14

8120FF

Female quick coupling BSPP thread



CODE	THREAD	LENGTH	WRENCH
8120FF01	G 1/8"	38,9	14
8120FF02	G 1/4"	40,7	15

8130RE

Quick coupling with barb connector



CODE	INTERNAL TUBE Ø	BARB	LENGTH	WRENCH
8130RE06	6	6,3	49,0	14
8130RE08	8	8,3	49,0	14

8140CA

Quick coupling with push-on connector



CODE	Ø	LENGTH	WRENCH
8140CA46	4x6	42,9	14
8140CA68	6x8	43,6	14
8140CA810	8x10	45,0	14



8150MO

Quick coupling with push-on connector and spring



CODE	Ø	LENGTH	WRENCH 1	WRENCH 2
8150MO46	4x6	115,6	14	12
8150MO68	6x8	128,3	14	13
8150MO810	8x10	129,2	14	15

8155BU

Bulkhead quick coupling with push-on connector



CODE	Ø	LENGTH	WRENCH 1	WRENCH 2
8155BU46	4x6	57,7	14	12
8155BU68	6x8	58,0	17	14

8160MM

Male connection BSPP thread



CODE	THREAD	LENGTH	WRENCH
8160MM01	G 1/8"	26,0	12
8160MM02	G 1/4"	28,4	14

8170FM

Female connection BSPP thread



CODE	THREAD	LENGTH	WRENCH
8170FM01	G 1/8"	26,0	12
8170FM02	G 1/4"	28,4	14



8180RE

Connection with barb connector



CODE	INTERNAL TUBE Ø	BARB	LENGTH
8180RE06	6	6,4	33,0
8180RE08	8	8,5	34,5

8190CA

Connection with push-on connector



CODE	Ø	LENGTH	WRENCH
8190CA46	4x6	32,5	12
8190CA68	6x8	33,1	12
8190CA810	8x10	34,7	14

8195MO

Connection with push-on connector and spring



CODE	Ø	LENGTH	WRENCH 1	WRENCH 2
8195MO46	4x6	104,3	12	12
8195MO68	6x8	117,0	12	12
8195MO810	8x10	120,4	14	15

