

TECHNICAL TUBES

POLYURETHANE
TUBE WITH
NON-TOXIC PVC
INNER LAYER

PLUS

**EXCELLENT FLEXIBILITY AND
LIGHTNESS FOR IMPROVED
ERGONOMICS**

**SUITABLE FOR PNEUMATIC TOOLS,
PAINT GUNS AND AIRBRUSHES**

NON-TOXIC PVC INNER LAYER

**MAINTAINS A GOOD SEAL OVER
TIME**





p. 751 / **PU-PVC**





-20°C ÷ 60°C



Working pressure:

20 Bar

Burst pressure:

60 Bar



Compressed air, vacuum and fluids suitable with construction materials



Inner layer: Transparent PVC in special blend

Reinforcement: Synthetic textile insert

Outer layer: PVC with polyurethane

SILICONE FREE



Products in compliance with EC Regulation 1907/2006



Products in compliance with the directive EU 2015/863

PU-PVC

Polyurethane tube with non-toxic PVC inner layer



CODE	Ø IDxOD	THICKNESS (mm)	MIN. BENDING RADIUS (mm)	WORKING PRESSURE (Bar)	BURSTING PRESSURE (Bar)	g/m	Q.TY FOR ROLL (mt)
PU-PVC0610	6x10	2	55	20	60	65	100
* PU-PVC0812	8x12	2	65	20	60	80	100
* PU-PVC1015	10x15	2,5	68	20	60	100	100
PU-PVC1016	10x16	3	70	20	60	155	100
PU-PVC1319	13x19	3	105	20	60	180	100

* Sizes suitable for use with fittings 1295 on page 287



Sizes Ø IDxOD		
	Light blue	
6x10	PU-PVC0610AZ	
8x12	PU-PVC0812AZ	
10x15	PU-PVC1015AZ	
10x16	PU-PVC1016AZ	
13x19	PU-PVC1319AZ	

